

Super FoamFast No. 74

Spray Adhesive

Convenient spray adhesive for smaller coverage areas, installations in tight spaces and quick repairs.



Available in: **Single - 16 oz. Cans**
 Cases of 12 - 16 oz. Cans

- Excellent adhesion of (acoustic) foam to foam and foam to a wide variety of surfaces including metal, wood, including metal, wood, glass. May also be used with flexible and rigid fiberglass.
- Non-misting controlled lace spray coating. Adhesive can be applied without the risk of overspray marring the surface of previously installed pieces.
- Two surface - contact type adhesive. Open time 30 sec. to 15 mins.
- Quick bonds with foam tearing strength.
- Coverage is approx. 100 sq. ft. per can or 2 (27 sq. ft.) sheets installed, two surface contact.

BASIC INSTALLATION INSTRUCTIONS

1. Use only in a well-ventilated area.
2. Make sure surfaces are free of dirt, grease and moisture.
3. Shake can well before use.
4. Align nozzle arrow with dot on top of can.
5. Hold can upright about 6" to 8" away from surface.
6. Test spray pattern in a protected area away from project surfaces.
7. Spray with a light, uniform coat.
8. Wait 30 seconds before securing the bond.
9. To help prevent clogged nozzles after use, tip can upside down and spray until adhesive does not emit.